

# FICHE TECHNIQUE


## COUDE 45° • E45

Utilisé pour dévier le carneau ou la cheminée de 45°.

**Inclus :**

- 1 Bande d'assemblage (AB)
- 1 Bande de finition (FB)

K = 0.15



DOUBLE PAROI - 2''							
D.I.		A		B		C	
po	mm	po	mm	po	mm	po	mm
6	152	26.235	666	6.993	178	19.243	489
8	203	19.064	738	7.407	188	21.657	550
10	254	31.892	810	7.821	199	24.071	611
12	305	34.721	882	8.235	209	26.485	673
14	356	37.549	954	8.649	220	28.889	734
16	406	40.377	1026	9.024	230	31.314	795
18	457	43.206	1097	9.478	241	33.728	857
20	508	46.034	1169	9.892	251	36.142	918
22	559	48.863	1241	10.306	262	38.556	979
24	610	51.691	1313	10.721	272	40.971	1041
26	660	54.520	1385	11.135	283	43.385	1102
28	711	57.348	1457	11.549	293	45.799	1163
30	762	60.176	1528	11.963	304	48.213	1225
32	813	63.005	1600	12.377	314	50.627	1286
34	864	65.833	1672	12.792	325	53.042	1347
36	914	68.662	1744	13.206	335	55.456	1409
38	965	71.490	1816	13.260	346	57.870	1470
40	1016	74.319	1888	14.034	356	60.284	1531
42	1067	77.147	1960	14.448	367	62.628	1593
44	1118	79.975	2031	14.863	378	65.113	1654
46	1168	82.804	2103	15.277	388	67.527	1715
48	1219	85.632	2175	15.691	399	69.941	1777

DOUBLE PAROI - 4''							
D.I.		A		B		C	
po	mm	po	mm	po	mm	po	mm
6	152	27.485	698	8.743	222	18.743	476
8	203	30.314	770	9.157	233	21.157	537
10	254	33.142	842	9.571	243	23.571	599
12	305	35.971	914	9.985	254	25.985	660
14	356	38.799	985	10.399	264	28.399	721
16	406	41.627	1057	10.814	275	30.814	783
18	457	44.456	1129	11.228	285	33.228	844
20	508	47.284	1201	11.642	296	35.642	905
22	559	50.113	1273	12.056	306	38.056	967
24	610	52.941	1345	12.471	317	40.471	1028
26	660	55.770	1417	12.885	327	42.885	1089
28	711	58.598	1488	13.299	338	45.299	1151
30	762	61.426	1560	13.713	348	47.713	1212
32	813	64.255	1632	14.127	359	50.127	1273
34	864	67.083	1704	14.542	369	52.542	1335
36	914	69.912	1776	14.956	380	54.956	1396
38	965	72.740	1848	15.370	390	57.370	1457
40	1016	75.569	1919	15.784	401	59.784	1519
42	1067	78.397	1991	16.198	411	62.198	1580
44	1118	81.225	2063	16.613	422	64.613	1641
46	1168	84.054	2135	17.027	432	67.027	1702
48	1219	86.882	2207	17.441	443	69.441	1764

DISPONIBLE POUR LES MODÈLES:

IPPL/IPPL2/IPPL2F/IPPL4F

HEPL/HEPL2

GDPL/GDPL2F/GDPL4F